

# PRH-M | MINI RADIANT HEATERS

10 W - 30 W

NEW



The **PRH-M Mini-Radiant Heaters** are available in 3 models ranging from 10 W - 30 W. These small heaters are ideal for small outdoor enclosures, preventing condensate formation.

## Easy Mounting Options

Unit can be connected to a standard DIN rail **without tools** using the included snap fastener.

## Multiple Performance Ratings

The PRH-M is available in 3 different heating performance based models from 10 W to 30 W. Choose the total heat to be distributed based on your calculated requirements.

## Ultra Compact Design

At just slightly over 1" wide and under 3" tall, this compact design easily installs into areas that have a limited installation space.

## Durable Long-Lasting

With its rugged design, solid construction and no moving parts you can count on the PRH-M Heater to perform consistently over a long period of time.

## Reduced Installation Time

The PRH-M Heater supports multiple voltage and includes a hard wired 12" (300 mm) electronic cord to easily install within the electrical enclosure.

## UL Certified

Heaters are UL Recognized to NITW2 standards allowing for easy integration into UL 508A panels.

# FLH | RADIANT & FAN HEATERS

30 W - 400 W



The **FLH Heaters** are available as a radiant heater or as a forced air heater for larger wattages. These heaters are designed to protect electronics from low temperatures and moisture caused by high humidity or rapid temperature changes.

## Easy Mounting Options

Unit can be connected to a standard DIN rail **without tools** using the included snap fastener.

## Heat Distribution

Our larger FLH 250 and FLH 400 Heaters include a fan to help circulate the heat in larger enclosures, ensuring quick and even distribution.

## Durable Long-Lasting

With its rugged design and solid construction you can count on the FLH Heaters to perform consistently over a long period of time.

## Reduced Installation Time

Save time and money when installing or moving the unit with our UL listed quick connects.

## UL Certified

Heaters are UL Recognized allowing for integration into UL 508A panels.



### PRH-M Series (10 - 30 W) Mini Radiant (PTC) Heaters

Model Number	Part Number	Voltage (VAC)	Heating performance (W)*	Frequency (Hz)	Power Consumption (W)	Starting Current (A)	Width in (mm)	Depth in (mm)	Height in (mm)	Weight lb (kg)
<b>PRH 010-M</b>	17000105317	110-250	10	50/60	10	1.0	1.16 (29.5)	1.77 (45)	2.95 (75)	.19 (.09)
<b>PRH 020-M</b>	17000205317	110-250	20	50/60	20	1.1	1.16 (29.5)	1.77 (45)	2.95 (75)	.26 (.12)
<b>PRH 030-M</b>	17000305317	110-250	30	50/60	30	1.2	1.16 (29.5)	1.77 (45)	2.95 (75)	.26 (12)

**Design** Black anodized Aluminum

### FLH Series (10 - 150 W) Radiant Heaters - With extruded aluminum body

<b>FLH 030W</b>	17003005007	110-250	30	50/60	30	1.2	2.76 (70)	1.97 (50)	3.94 (100)	.55 (.25)
<b>FLH 045W</b>	17004505007	110-250	45	50/60	45	1.8	2.76 (70)	1.97 (50)	3.94 (100)	.55 (.25)
<b>FLH 060W</b>	17006005007	110-250	60	50/60	60	2.5	2.76 (70)	1.97 (50)	6.89 (175)	.99 (.45)
<b>FLH 075W</b>	17007505007	110-250	75	50/60	75	4.5	2.76 (70)	1.97 (50)	6.89 (175)	1.12 (.51)
<b>FLH 100W</b>	17010005007	110-250	100	50/60	100	5.0	2.76 (70)	1.97 (50)	6.89 (175)	1.12 (.51)
<b>FLH 150W</b>	17015005007	110-250	150	50/60	150	7.5	2.76 (70)	1.97 (50)	9.84 (250)	1.7 (.77)

### FLH Series (250 - 400 W) Fan Heaters - With extruded aluminum body

<b>FLH 250</b>	17025015007	115	250	60	260	2.2	3.35 (85)	4.09 (104)	7.34 (186.5)	2.29 (1.04)
	17025010007	230	250	50/60	260	1.1	3.35 (85)	4.09 (104)	7.34 (186.5)	2.29 (1.04)
<b>FLH 400</b>	17040015007	115	400	60	410	3.6	3.35 (85)	4.09 (104)	8.92 (226.5)	2.65 (1.20)
	17040010007	230	400	50/60	410	1.8	3.35 (85)	4.09 (104)	8.92 (226.5)	2.65 (1.20)

**Design** Aluminum profile, brightly anodized

\*Heating performance (Ta = +68 °F/+20 °C)

Approvals (see the Quick Selection Chart found at the beginning of this section)



For additional technical data, drawings and manuals.

[www.pfannenbergsusa.com](http://www.pfannenbergsusa.com)

#### Available Models:

**PRH-M**  
Ultra Compact Design  
(Integrated Cord)



**FLH**  
Compact & Large Designs  
(Quick Connects)

