

FTTA.E489500 - Environmental-rated Accessories for Enclosures

Note: We are enhancing our systems and you may notice duplicate entries/missing/outdated data. During this interim period, please contact our Customer Service at <https://www.ul.com/about/locations>.

Environmental-rated Accessories for Enclosures

[See General Information for Environmental-rated Accessories for Enclosures](#)

PFANNENBERG GMBH

Werner-Witt-Strasse 1
21007 Hamburg, GERMANY

E489500

Part No.	Environmental Type Rating	Standard	IEC 60529 IP Rating
Filter fan kits			
PF followed by 11, 22, 32, 43, 65, 66, 67 followed by 000 with or without additional suffix. DPF followed by 11, 22, 32, 43, 65, 66, 67 followed by 000 with or without additional suffix. (Designation D identifies externally mounted). PF 33.000 SL, PF 65.000 SL, PF 67.000 SL. PF 42500 with or without additional suffix. PFA 10, 20, 30, 40, 60 followed by 000, with or without additional suffix DPFA followed by 10, 20, 30, 40, 60, followed by 000 with or without additional suffix. (Designation D identifies externally mounted).	1, 12	UL508	N/A
PF followed by 22, 32, 43, 65, 66, 67, maybe followed by ".", followed by 000 with additional suffix R. Model PF 42500 with or without additional suffix, may be followed by R. PFA followed by 20, 30, 40, 60, maybe followed by ".", followed by 000 with additional suffix R.	1, 12, 3R	UL 508	N/A
PTF 60500. PTF 60700. PTF 61000. PTFA 60000.	1, 12	UL508	N/A
Rain Hood Assembly			
PF-SH, followed by 20000, 30000, 40000 or 60000, followed by WD or XX, may be followed by YY PF-RH, followed by 20000, 30000, 40000 or 60000, followed by WD or XX, may be followed by YY.	3R, 4, 4X, 12 (See Note 1)	UL508A	N/A

PKS Cooling Series			
124 followed by X, followed by XX, followed by X, followed by X, followed by XX, followed by X	3R, 4, 4X, 12	ANSI/UL 50, ANSI/UL 50E	N/A

Note 1: To be used in combination with the following Listed FTTA (E489500) and R/C NITW2 (E175229) Pfannenberg Filter fan fits:

PF followed by 11, 22, 32, 43, 65, 66, 67 followed by 000 with or without additional suffix.

PF 33.000 SL, PF 65.000 SL, PF 67.000 SL.

PF 42500 with or without additional suffix.

PFA 10, 20, 30, 40, 60 followed by 000, with or without additional suffix.

Last Updated on 2020-12-22

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"